

# IP VIDEO INTERCOMS

Sense of safety



# The perfect solution for single-family houses!



# **IP VIDEO INTECOMS**

Quick and easy system scaling thanks to IP technology



ONE-BUTTON IP ENTRANCE PANEL WITH WI-FI

**NVE-EPV101P** 

**ONE-BUTTON IP ENTRANCE PANEL** 

NVE-EPV102P

TWO-BUTTONS IP ENTRANCE PANEL

**NVE-MV107WIFI** 

7" IP USER MONITOR WITH WI-FI

**NVE-MV110WIFI** 

10,1" IP USER MONITOR WITH WI-FI

# Professional and modern NOVUS video intercom system. The perfect solution for single-family houses!

twin houses

single-family houses

single-family houses with belonging business








APPLICATIONS:

home + home office


house with business activity

home + workshop / beauty salon / accounting office etc.

### SYSTEM CAPABILITIES - SINGLE-FAMILY HOUSE



### YSTEM CAPABILITIES – TWIN HOUSE



# VIDEO INTERCOMS

# **NOVUS SERIES 100**











- 2 ON/OFF button
- 3 Micro SD card slot
- 4 Power/Message indicator
- 5 Home button (Back to main screen/ turn off the screen)



### **ACCESSORIES**















# BENEFITS

#### **HYBRID SYSTEM**

Clean and convenient installation without forging or laying wires. The NVE-EPV101KPWIFI monitors and panel support Wi-Fi technology, so they can work in a wireless network.

#### **CAMERAS PREVIEW**

Integration with the VSS system allows to display up to 8 video streams which can be viewed through the TuYa Smart APP.

#### **DVR FUNCTION**

Once detected, the monitors or panel \* will record video for 1 minute followed by one minute pause. After another detection occurs, the system will record video for 1 minute. Only the first 4 streams added to the monitor can be recorded. Streams 5-8 can only be previewed.

#### **REGISTRATION OF GUESTS**

Each attempt to connect with the household members can be saved in the device memory as a photo or a minute video recording with sound.

#### **VOICEMAIL**

Voice messages can be saved in the SD card memory. If the call is not answered, the message is recorded (when this function is turned on).



#### **HIGH-QUALITY AUDIO**

High quality audio during a call, both during a conversation via the monitor and the application.

#### **INTERCOM**

Possibility to connect to any monitor in the same apartment. Possibility to connect with other monitors in the same network and support for SIP / VoiP connections.

#### DOOR/GATE CONTROL

The entrance panels have 2 independent relays from the door and the gate, while an additional bell can be connected to the subscriber's monitor.

#### **TUYA SMART MOBILE APP**

The Tuya Smart APP allows to control the relays of the entrance panels and receive alarm notifications on your smartphone. The application also allows you to view all streams added to monitors

## MORE **FUNCTIONALITIES**



Motion and / or human detection \* (alarm notifications)



Possibility to send a voice message on all monitors in a given apartment



Unlock with password \*\*



Possibility to listen to sounds from the surroundings of the selected monitor



Record photos and videos during a call



Night mode.
Possibility to set
the hours when the
monitor will have a
different volume



5 alarm clocks. 5 times can be set



Wide (120°) viewing angle



Memory for up to 100 proximity cards



SD card. Support for Class 10 cards with a capacity from 8 to 128 GB



Simple device adding based on DHCP



Digital frame or digital clock function



Personalization: the possibility to upload your ringtone and wallpaper



Powered by PoE/15 VDC **IP66** 

The entrance panels have IP66 weather resistance

\*Human detection function available in dedicated panels; \*\* NVE-EPV101KPWIFI; \*\*\* NVE-EPV101KPWIFI is powered by passive 24V PoE



## IR BACKLIGHT

TOUCH KEYBOARD

IP66 IP CODE





## **MOBILE** APP

Wherever you are, whatever you are doing, use the mobile app to see who is going to visit you



- redirecting calls from panels to the application and the possibility of talking to guests
- playback of recordings from the internal memory of monitors or panels \*
- > door, gate control
- preview from panels and IP cameras with the possibility of saving photos and recording videos
- > **PUSH alarm notifications** for motion detection function

\*NVE-EPV101KPWIFI

# You don't have to rush with the mobile app!

Install TuYa Smart and keep everything under control!

- > redirect communication from the user monitor directly to your phone
- > receive instant notifications about detected motion, see who is calling, open the gate or door



## **TECHNICAL SPECIFICATION**

#### **NVE-MV107WIFI**





#### **NVE-MV110WIFI**





DEVICE TYPE	IP user monitor	IP user monitor		
DISPLAY	LCD TFT	LCDTFT		
RESOLUTION	1024 x 600 px	1024 x 600 px		
DIAGONAL	7"	10.1"		
POWER	15 VDC, PoE (802.3af)	15 VDC, PoE (802.3af)		
ADDITIONAL FEATURES	SD card slot, volume control, image preview from IP panels and cameras, intercom calls, text messages, voicemail, saving photos and recording videos, connection to the mobile application via WIFI, bell button, LED indicators	SD card slot, volume control, image preview from IP panels and cameras, intercom calls, text messages, voicemail, saving photos and recording videos, connection to the mobile application via WIFI, bell button, LED indicators		
POWER CONSUMPTION	8 W (Max)	8 W (Max)		
TEMPERATURE	from -10 to 50 ℃	from -10 to 50 °C		
DIMENSIONS	188 x 136 x 22 mm	255 x 180 x 21 mm		

#### Dedicated accessories:





NVS-3304SP 4-port PoE switch



#### **NVE-EPV101P**



DEVICETYPE	IP entrance panel		
NO. OF USERS	1		
IMAGE SENSOR	CMOS HD 2 MPx		
VIEWING ANGLE	120°		
RESOLUTION	1920 x 1080 px		
FUNCKJE DODATKOWE	IR LED, mounting on angle bracket, LED indicators		
PROXIMITY CARDS READER	Unique 125 KHz		
POWER	15 VDC, PoE (802.3af)		
POWER CONSUMPTION	4,5 W (Max)		
TEMPERATURE	from -40 to 60 °C		
IP CODE	IP66		
DIMENSIONS	154 x 55 x 21 mm		
OUTPUT	2 x NO relay (4 A / 36 V DC/AC)		

#### **NVE-EPV102P**



IP entrance panel
2
CMOS HD 2 MPx
120°
1920 x 1080 px
IR LED, mounting on angle bracket, LED indicators
Unique 125 KHz
15 VDC, PoE (802.3af)
4,5 W (Max)
from -40 to 60 °C
IP66
154 x 55 x 21 mm
2 x NO relay (4 A / 36 V DC/AC)

#### **NVE-101KPWIFI**



IP entrance panel				
1				
CMOS HD 2 MPx				
120°				
1920 x 1080 px				
IR LED, mounting on angle bracket, LED indi- cators, numeric keypad, access code, WiFi Dual Band, Standalone Mode, Bell Output				
Unique 125 KHz				
15 VDC, 24 V POE (tylko SV100)				
4,5 W (Max)				
from -40 to 60 ℃				
154 x 55 x 21 mm				
2 x NO relay (4 A / 36 V DC/AC)				

#### Dedicated accessories:





NVE-BRV100COR Angle bracket 28 °



NVE-PV100 Power supply



NVS-3304SP 4-port PoE switch



NVS-3308SP-DIN 8-port PoE switch with mounting on DIN rail

Distril	bution:			

